SOLID-STATE ELECTRONICS

AN INTERNATIONAL JOURNAL

List of Contents and Author Index Volume 35, 1992



PERGAMON PRESS

OXFORD · NEW YORK · SEOUL · TOKYO

SOLID-STATE ELECTRONICS

EDITORS

DR W. CRAWFORD DUNLAP (Editor-in-Chief)
126 Prince Street, West Newton, MA 02165, U.S.A., Fax: 617-244-1037

R. W. BRANDER

High Trees, Bucklesham Road, Foxall, Ipswich, Suffolk IP10 0AA, U.K.

DR F. M. KLAASSEN

Philips Research Laboratories, Eindhoven, The Netherlands

HONORARY EDITORIAL ADVISORY BOARD

R. H. BUBE, Stanford, CA

C. BULUCEA, Santa Clara, CA

U. BÜRKER, Munich

T. Y. CHIU, Holmdel, NJ

L. F. EASTMAN, Ithaca, NY

D. K. FERRY, Tempe, AZ

J. G. Fossum, Gainesville, FL

S. K. GHANDHI, Troy, NY

G. I. HADDAD, Ann Arbor, MI

R. HECKINGBOTTOM, Ipswich

H. K. HENISCH, University Park, PA

A. C. IPRI, Princeton, NJ

A. K. JONSCHER, Egham Hill

R. W. KNEPPER, East Fishkill, NY

A. G. MILNES, Pittsburgh, PA

B. R. NAG, Calcutta

H. C. NATHANSON, Pittsburgh, PA

A. Nussbaum, Minneapolis, MN

W. G. OLDHAM, Berkeley, CA

J. I. PANKOVE, Boulder, CO

J. E. PARROTT, Cardiff

R. F. PIERRET, W. Lafayette, IN

G. J. REES, Sheffield

B. RIDLEY, Colchester

H. Rотн, Hanscom, MA

D. J. ROULSTON, Waterloo, Ont.

C. A. T. SALAMA, Toronto, Ont.

R. STRATTON, Dallas, TX

R. VAN OVERSTRAETEN, Leuven

C. J. VARKER, Scottsdale, AZ

C.-Y. Wu, Hsinchu, R.O.C.

Publishing Office

Pergamon Press Ltd, Pergamon House, Bampfylde Street, Exeter EX1 2AH, England (Tel. Exeter (0392) 51558; Fax (0392) 425370).

Subscription and Advertising Offices

North America: Pergamon Press Inc., 660 White Plains Road, Tarrytown, NY 10591-5153, U.S.A. Rest of the World: Pergamon Press Ltd, Headington Hill Hall, Oxford OX3 0BW, England (Tel. Oxford (0865) 794141).

Subscription Rates

Annual institutional subscription rate (1993): £558.00 (US\$1060.00). Sterling prices are definitive. U.S. dollar prices are quoted for convenience only, and are subject to exchange rate fluctuation. Prices include postage and insurance and are subject to change without notice.

Back Issues

Back issues of all previously published volumes, in both hard copy and on microform are available direct from Pergamon Press offices.

Published monthly. Copyright © 1992 Pergamon Press Ltd

Second class postage paid at RAHWAY NJ. Postmaster send address corrections to Pergamon Press Inc., 660 White Plains Road, Tarrytown, NY 10591-5153, U.S.A.

LIST OF CONTENTS

NUMBER 1

| T. C. Lu and J. B. Kuo: An analytical pull-up transient model for a BiCMOS inverter | 1 |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|
| M. J. DEEN and Z. X. YAN: A simple propagation delay model for BiCMOS driver circuits | 9 |
| J. J. LIOU and H. SHAKOURI: Collector signal delay time and collector transit time of HBTs including velocity overshoot | 15 |
| J. H. Zhao, P. F. Tang and J. Jeong: Compositional dependence of Schottky barrier heights of Au on MBE grown GaAs _{1-x} Sb _x | 21 |
| A. T. Wu, S. W. Lee, T. Y. Chan and V. Murali: Temperature and field dependence of carrier mobility in MOSFETs with reoxidized nitrided oxide gate dielectrics | 27 |
| HONGCHIN LIN, NEIL GOLDSMAN and I. D. MAYERGOYZ: An efficient deterministic solution of the space-dependent Boltzmann transport equation for silicon | 33 |
| S. Huber and W. Harth: Low-frequency open-circuit noise voltage of GaAs pin-avalanche transit-time diodes | 43 |
| A. AFZALI-KUSHAA and M. EL NOKALI: Modeling subthreshold capacitances of MOS transistors | 45 |
| H. S. HAJGHASSEM, W. D. BROWN and J. G. WILLIAMS: Modeling the effects of neutron irradiation on LEDs | 51 |
| G. B. GAO, M. S. ÜNLÜ, J. CHEN, B. MAZHARI, K. ADOMI, G. X. LIU, Z. F. FAN and H. MORKOÇ: Double-layer collector for heterojunction bipolar transistors | 57 |
| Andrzej Wolkenberg, Tomasz Przesławski and Jerzy Klamka: Measurement of the resistance of metal-semiconductor-metal structures using the geometrical magneto-resistance technique | 61 |
| M. P. Houng, Y. H. Wang, H. H. Chen and C. C. Pan: The negative differential resistance behavior of GaAs delta-doped structures | 67 |
| J. A. LOPEZ-VILLANUEVA, J. A. JIMENEZ-TEJADA, P. CARTUJO, J. BAUSELLS and J. E. CARCELLER: A high-frequency bidirectional capacitance method to study the evolution of the interface state density generated at low temperatures | 73 |
| X. LETARTRE and D. STIEVENARD: Electrical behaviour of a sheet of defects | 83 |
| TAKAYA MIYANO, MANABU FUJITO, MASAHIRO KATO and HIROYUKI TSUGE: A mechanism for impact ionization of Si n-channel MOSFETs | 89 |
| Z. J. MA, Z. H. LIU, P. T. LAI, S. FLEISCHER and Y. C. CHENG: Impact of nitridation/reoxidation on performance degradation in <i>n</i> -MOSFETs under Fowler-Nordheim | |
| njection | 95 |

| E. E. CLARKE, F. N. TROFIMENKOFF and J. W. HASLETT: High-temperature silicon diode models | 103 |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|
| Note HAOSHENG ZHOU and D. L. PULFREY: Computation of transit and signal delay times for the collector depletion region of GaAs-based HBTs | 113 |
| SOFTWARE SURVEY SECTION | I |
| NUMBER 2 | |
| WEN-SHIUNG LOUR, WEN-CHAU LIU and YEONG-HER WANG: Investigation of hetero- structure-confinement-emitter transistors | 117 |
| D. B. M. KLAASSEN, J. W. SLOTBOOM and H. C. DE GRAAFF: Unified apparent bandgap narrowing in n- and p-type silicon | 125 |
| T. J. BORDELON, XL. WANG, C. M. MAZIAR and A. F. TASCH: Accounting for bandstructure effects in the hydrodynamic model: a first-order approach for silicon device simulation. | 131 |
| THIERRY OUISSE, SORIN CRISTOLOVEANU and GÉRARD BOREL: Influence of series resistances and interface coupling on the transconductance of fully-depleted silicon-on-insulator MOSFETs | 141 |
| L. He and W. A. Anderson: A study of defects induced in GaAs by plasma etching | 151 |
| M. Porges and T. Lalinsky: Characterization of planar ohmic contacts—the effect of position of probes on contact area | 157 |
| HOUNG-CHI WEI, YEONG-HER WANG and MAU-PHON HOUNG: Effects of base-emitter junction on the resonant tunneling bipolar transistor with double barriers in the emitter | 159 |
| A. HINTZ and K. SCHÜNEMANN: Improved balance equations for modeling non-stationary transport and the electron distribution function in GaAs | 165 |
| X. H. Fu and J. N. Chen: A point-by-point multiple-sweep numerical algorithm for dopant profiling based on $C-V$ data | 181 |
| QIN HUANG, GEHAN A. J. AMARATUNGA and WILLIAM I. MILNE: MOS controlled current interruption | 187 |
| A. D. SADOVNIKOV and A. V. TCHERNYAEV: Two-dimensional model of impurity diffusion in polysilicon-silicon structures | 193 |
| TERRY S. Ma and WAYNE B. GRABOWSKI: Junction breakdown analysis of a floating field-limiting ring structure using a PISCES-2B device simulator | 201 |
| XIUMIAO ZHANG: Determination of the profile of the bulk generation lifetime from pulsed MOS-C transients | 207 |
| T. JOHANSSON, K. JARL and M. WILLANDER: Power amplifier for ultra high frequency using conventional silicon NMOS IC technology | 213 |

| Notes A. M. IBRAHIM and MAGDY M. IBRAHIM: Modelling of velocity overshoot in submicron | 154-50 |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|
| semiconductor devices | 221 |
| BOGDAN MAJKUSIAK and ANDRZEJ JAKUBOWSKI: A technical formula for determining the insulator capacitance in a MOS structure | 223 |
| P. Chakrabarti, Tanmay Kumar, Arun Kumar and B. R. Narasimha Prasad: Numerical simulation for estimating $C-V$ characteristics of MODFETs under illumination | 225 |
| László Dózsa: A new method to measure fast defect transients in semiconductor and/or insulator samples | 228 |
| Announcements | I |
| SOFTWARE SURVEY SECTION: GIGA, SOLID, PRISM, LUMINOUS and OPTIC2 | Ш |
| NUMBER 3 | |
| SOLID-STATE DEVICE AND MATERIAL MEASUREMENTS | 5 |
| ROBERT F. PIERRET and DIETER K. SCHRODER: Foreword | v |
| I. MEASUREMENTS UTILIZING AN OPTICAL PROBE/OPTICAL EXCITAT | ION |
| Invited Papers V. A. Burrows: Internal reflection infrared spectroscopy for chemical analysis of surfaces and thin films | 231 |
| R. K. Ahrenkiel: Measurement of minority-carrier lifetime by time-resolved photo- luminescence | 239 |
| M. L. LOVEJOY, M. R. MELLOCH, R. K. AHRENKIEL and M. S. LUNDSTROM: Measurement considerations for zero-field time-of-flight studies of minority carrier diffusion in III-V semiconductors | 251 |
| E. YABLONOVITCH and T. J. GMITTER: A contactless minority lifetime probe of heterostructures, surfaces, interfaces and bulk wafers | 261 |
| Regular Papers S. C. Choo, L. S. Tan and K. B. Quek: Theory of the photovoltage at semiconductor surfaces and its application to diffusion length measurements | 269 |
| J. BARBOLLA, S. DUEÑAS and L. BAILÓN: Admittance spectroscopy in junctions | 285 |
| V. GRIVICKAS, J. LINNROS, A. VIGELIS, J. ŠEČKUS and J. A. TELLEFSEN: A study of carrier lifetime in silicon by laser-induced absorption: a perpendicular geometry measurement. | 299 |
| F. Sanii, F. P. Giles, R. J. Schwartz and J. L. Gray: Contactless nondestructive measurement of bulk and surface recombination using frequency-modulated free carrier | 211 |
| absorption | 311 |

vi

| M. G. MIER, D. C. LOOK, D. C. WALTERS and D. L. BEASLEY: Infrared transmission topography for whole-wafer gallium arsenide materials characterization | 319 |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|
| M. Y. Frankel, J. F. Whitaker, G. A. Mourou and J. A. Valdmanis: Ultrahigh-bandwidth vector network analyzer based on external electro-optic sampling | 325 |
| H. Reisinger: Minimization of errors in ellipsometric measurements | 333 |
| II. MOS/SOI PARAMETER MEASUREMENTS | |
| Invited Papers STEVEN C. WITCZAK, JOHN S. SUEHLE and MICHAEL GAITAN: An experimental comparison of measurement techniques to extract Si-SiO ₂ interface trap density | 345 |
| TOSHIKAZU NISHIDA: BiMOS and SMOSC structures for MOS parameter measurement | 357 |
| Regular Papers HUNG-SHENG CHEN and SHENG S. LI: Determination of generation lifetime and interface state density using a pulsed silicon-insulator-silicon capacitor | 371 |
| M. Kerber, C. Mazuré and U. Schwalke: Measurement of the threshold voltage in MOS capacitors by the equilibrium controlled static $C-V$ method | 379 |
| PLAMEN KOLEV: An improved feedback circuit for constant-capacitance voltage transient measurements | 387 |
| III. IC METROLOGY AND MISCELLANEOUS MEASUREMENTS | |
| Invited Papers TIMOTHY R. CORLE: Submicron metrology in the semiconductor industry | 391 |
| HARRY A. SCHAFFT and JOHN S. SUEHLE: The measurement, use and interpretation of the temperature coefficient of resistance of metallizations | 403 |
| T. M. Moore: C-Mode acoustic microscopy applied to integrated circuit package inspection | 411 |
| J. J. KOPANSKI, J. R. LOWNEY, D. S. MILES, D. B. NOVOTNY and G. P. CARVER: High spatial resolution mapping of resistivity variations in semiconductors | 423 |
| Regular Papers R. A. Allen and M. W. Cresswell: Elimination of effects due to patterning imperfections in electrical test structures for submicrometer feature metrology | 435 |
| S. E. FISCHER, J. L. SNARE and P. T. NGUYEN: Profiling the bandgap-adjusted mobility in a bipolar transistor base using the inverse Early effect | 443 |
| NUMBER 4 | |
| F. J. SCHOLZ and J. W. ROACH: Low-frequency noise as a tool for characterization of near-band impurities in silicon | 447 |

| Contents | vi |
|----------|----|
| | |

| M. H. Juang and H. C. Cheng: Formation of shallow p^+n junctions by implanting BF_2^+ ions into thin cobalt films on silicon substrates | 453 |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|
| G. HALKIAS, A. VEGIRI, G. PANANAKAKIS and A. CHRISTOU: Efficient charge control model for pseudomorphic and strained high electron mobility transistors on GaAs and InP substrates. | 459 |
| Douglas E. Dunn and Carlos A. Paz de Araujo: GAVELS, a velocity-space GaAs transport model—I. Steady-state simulation | 467 |
| Douglas E. Dunn: GAVELS, a velocity-space GaAs transport model—II. Velocity overshoot simulation | 477 |
| O. Bonnaud, M. Sahnoune, A. Solhi and H. Lhermite: Modeling the base current of an a-Si: H/c-Si heterojunction bipolar transistor | 483 |
| S. T. Fu and M. B. Das: Modeling of the source resistance in modulation-doped FETs | 489 |
| Wen-Chau Liu and Der-Feng Guo: A new GaAs switching device with double-confinement-collector structure | 501 |
| MINGHUI GAO, JEAN-PIERRE COLINGE, LODE LAUWERS, SUHUA WU and COR CLAEYS: Twin-MOSFET structure for suppression of kink and parasitic bipolar effects in SOI MOSFETs at room and liquid helium temperatures | 505 |
| Q. CHEN and M. WILLANDER: Relationship between measured and intrinsic trans- conductances for FETs with gate conduction | 513 |
| D. J. DUMIN, J. R. COOPER, K. J. DICKERSON and G. A. BROWN: The polarity, field and fluence dependence of interface trap generation in thin silicon oxide | 515 |
| MENG-CHYI WU, CHI-CHING CHEN and CHING-TING LEE: Growth and characterization of high-quality GaInAsSb layers on GaSb substrates by liquid-phase epitaxy | 523 |
| R. ALCUBILLA, J. Pons and L. Castañer: Superposition solution for minority carrier current in the emitter of bipolar devices | 529 |
| G. S. VIRDI, C. M. S. RAUTHAN, B. C. PATHAK, W. S. KHOKLE, S. K. GUPTA and KRISHAN LAL: On the role of fluorine in BF ₂ ⁺ implanted silicon | 535 |
| WILLIAM LIU, DAMIAN COSTA and J. S. HARRIS JR: Derivation of the emitter-collector transit time of heterojunction bipolar transistors | 541 |
| WILLIAM LIU, DAMIAN COSTA and J. S. HARRIS JR: A simplified model for the distributed base contact impedance in heterojunction bipolar transistors | 547 |
| S. C. CHEN, Y. K. Su and C. Z. Lee: Collector-emitter offset voltage in single- and double-base InGaAs(P)/InP heterojunction bipolar transistors | 553 |
| SHIN-CHI LEE and TING-WEI TANG: Transport coefficients for a silicon hydrodynamic model extracted from inhomogeneous Monte-Carlo calculations | 561 |
| R. VANKEMMEL, W. SCHOENMAKER, R. CARTUYVELS, K. APPELTANS and K. DE MEYER: Implementation of heterojunctions into the 2-D finite-element simulator PRISM: some scaling considerations | 571 |

viii Contents

| L. L. LIOU, C. I. HUANG and J. EBEL: Numerical studies of thermal effects on heterojunction bipolar transistor current-voltage characteristics using one-dimensional simulation | 579 |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|
| P. CHAKRABARTI, R. ANAND and V. SRINIVASA RAO: I-V Characteristics of an optically controlled Si-MESFET | 587 |
| S. R. Shukla and M. N. Sen: Analytical expressions for the drift velocity of hot charge carriers in silicon | 593 |
| J. WENG: Transit time of fast bipolar transistors at high collector-current densities | 599 |
| Announcement | 1 |
| SOFTWARE SURVEY SECTION | III |
| | |
| NUMBER 5 | |
| D. X. Xu, G. D. Shen, M. WILLANDER, F. Schäffler and J. F. Luy: Experimental studies on the NDR of $Si_{1-x}Ge_x/Si$ triple barrier resonant tunneling diodes | 611 |
| SHENG-LYANG JANG and KUANG-LANG CHERN: Breakdown characteristics of emitter-base and collector-base junctions of silicon bipolar junction transistors | 615 |
| H. C. Tseng and Sheng S. Li: Negative differential conduction (NDC) in $n^+-v-p^+-v-n^+$ AlGaAs/GaAs heterojunction devices | 623 |
| J. B. Kuo, C. C. Chang and T. C. Lu: A poly-emitter BJT Gummel-Poon model for pull-up transient analysis of a BiCMOS inverter | 629 |
| W. C. Hsu and H. M. Shieh: A δ -doped GaAs/In _{0.37} Ga _{0.63} As/GaAs high electron mobility transistor prepared by low-pressure metalorganic chemical vapor deposition | 635 |
| S. C. JAIN, J. M. McGregor, D. J. ROULSTON and P. BALK: Modified simple expression for bandgap narrowing in <i>n</i> -type GaAs | 639 |
| S. L. Chen and Jeng Gong: Influence of drain bias voltage on determining the effective channel length and series resistance of drain-engineered MOSFETs below saturation | 643 |
| S. DECOUTERE, L. DEFERM, C. CLAEYS and G. DECLERCK: Modeling the non-uniformity of base sheet resistivity at high currents in bipolar transistors | 651 |
| Young Hee Byun, Michael Shur, Michael Hack and Kwyro Lee: New analytical polycrystalline-silicon thin-film transistor model for computer aided design and parameter extraction | 655 |
| O. VANBESIEN, H. LEROUX and D. LIPPENS: Maximally flat transmission windows in finite superlattices | 665 |
| Konstantin Nikolić: Steady-states in a cooled p-Ge photoconductor via the Landsberg-Schöll-Shukla model | 671 |
| MICHAEL REISCH: Self-heating in BJT circuit parameter extraction | 677 |

| T. LASKA, G. MILLER and J. NIEDERMEYR: A 2000 V non-punchthrough IGBT with high ruggedness | 681 |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|
| Q. Chen and M. Willander: Analytical d.c. and small-signal a.c. modeling of Si delta(δ)-doped field effect transistors | 687 |
| Y. L. LE Coz and H. F. TIERSTEN: Ehrenfest derivation of forces acting within semiconductors of inhomogeneous material composition | 695 |
| P. Van Mieghem, S. Decoutere, G. Borghs and R. Mertens: Influence of majority carrier bandtails on the performance of semiconductor devices | 699 |
| CHING-YUAN WU and CHIOU-FENG CHEN: Physical model for characterizing and simulating a FLOTOX EEPROM device | 705 |
| TOMASZ SKOTNICKI, GÉRARD MERCKEL and CHRISTIAN DENAT: Triggering and sustaining of snapback in MOSFETs | 717 |
| J. S. Wu, C. P. Lee, C. Y. Chang, K. H. Chang, D. G. Liu and D. C. Liou: Intrinsic and extrinsic effects on performance limitation of AlGaAs/GaAs double-barrier resonant tunneling structures | 723 |
| M. A. AMATO: Thermal excitation rates and capture cross sections associated with deep impurities in semiconductors | 731 |
| A. R. BATCHELOR: On the design of doping concentration profiles for GaAs transferred- electron device layers | 735 |
| Notes A. R. BATCHELOR, R. E. MILES and M. J. Howes: On the relative advantages of modelling semiconductors using a non-isothermal analysis | 743 |
| WILLIAM H. HAYDL: Highly forward-biased FET gates and their experimental current and voltage distributions. | 747 |
| K. F. KNOTT: Direct observation of intermediate levels in multistep burst noise | 749 |
| SOFTWARE SURVEY SECTION | I |
| | |
| NUMBER 6 | |
| CHUNG-YIH SUN and WEN-CHAU LIU: A new GaAs bipolar transistor with a doping-superlattice collector | 751 |
| IBRAHIM M. ABDEL-MOTALEB and C. N. LI: Nonlinear model for MODFET parasitic resistances | 759 |
| HONGCHIN LIN, NEIL GOLDSMAN and I. D. MAYERGOYZ: Device modeling by deterministic self-consistent solution of Poisson and Boltzmann transport equations | 769 |
| H. R. LIAUH, M. F. TSENG, M. C. CHEN and L. J. CHEN: Influence of contact treatments on the electrical characteristics of shallow-junction titanium-based contacts | 779 |

| T. C. Lu and J. B. Kuo: An analytical bandgap-narrowing-related current-gain model for BJT devices operating at 77 K | 785 |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|
| Y. PAN, S. C. JAIN, M. KLEFFSTRA and P. BALK: Modelling of band tails and their effects on minority carrier transport in heavily doped silicon | 791 |
| H. REISINGER, H. OPPOLZER and W. HÖNLEIN: Thickness determination of thin SiO ₂ on silicon | 797 |
| J. J. LIOU and J. S. YUAN: Surface recombination current of AlGaAs/GaAs hetero- junction bipolar transistors | 805 |
| W. PITTROFF, H. G. BACH and G. BEISTER: Numerical modelling of carrier profiles in isotype and anisotype heterojunction devices | 815 |
| S. Bellone, G. Cocorullo, F. G. Della Corte, H. L. Hartnagel and G. Schweeger: Analytical model for GaAs pin diodes for a wide range of currents and temperatures. | 821 |
| D. MISRA and V. S. SIMHADRI: A survey of the potential of an IrSi Schottky barrier MOSFET based on simulation studies | 829 |
| ABDULMECIT TÜRÜT, NECATI YALÇIN and MUSTAFA SAĞLAM: Parameter extraction from non-ideal $C-V$ characteristics of a Schottky diode with and without interfacial layer | 835 |
| R. R. SIERGIEJ, M. H. WHITE and N. S. SAKS: Theory and measurement of quantization effects on Si–SiO ₂ interface trap modeling | 843 |
| T. EASWARAKHANTHAN, Z. OUENNOUGHI and S. RAVELET: An inversion method for the complete characterization of transparent film-absorbing substrate systems using multiple angle ellipsometry | 855 |
| MASAAKI TOMIZAWA, TADAO ISHIBASHI, HERBERT S. BENNETT and JEREMIAH R. LOWNEY: Effects of heavy doping on numerical simulations of gallium arsenide bipolar transistors | 865 |
| Notes P. Chattopadhyay and B. Raychaudhuri: Origin of the anomalous peak in the forward capacitance-voltage plot of a Schottky barrier diode | 875 |
| L. B. CHANG, M. S. HUANG and S. F. LAI: Monolithic TJS light emitting device grown on SI GaAs substrate by LPE | 879 |
| Corrigendum | I |
| SOFTWARE SURVEY SECTION | III |
| NUMBER 7 | |
| I. AHMAD and S. AHMAD: Influence of a non-uniformly doped semiconductor region on Skin Effect Resistance of ohmic contacts in mm-wave IMPATTs | 883 |
| WILLIAM LIU and JAMES S. HARRIS JR: Parasitic conduction current in the passivation ledge of AlGaAs/GaAs heterojunction bipolar transistors | 891 |

| J. G. C. Bakker, J. Bisschop and W. H. A. Schilders: Current-voltage relation for abrupt N^+-P-N^+ and $N-i-N$ structures | 897 |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|
| Q. Kim, H. R. Schwartz, L. D. Edmonds and J. A. Zoutendyk: Diagnosis of NMOS DRAM functional performance as affected by a picosecond dye laser | 905 |
| J. RACKO, D. DONOVAL, M. BARUS, V. NAGL and A. GRMANOVA: Revised theory of current transport through the Schottky structure | 913 |
| J. S. Yuan: Modeling Si/Si _{1-x} Ge _x heterojunction bipolar transistors | 921 |
| PING-CHANG YANG and SHENG S. LI: Measurements of substrate carrier lifetimes in silicon-on-insulator wafers by a contactless dual-beam optical modulation technique | 927 |
| K. A. NEYTS and P. DE VISSCHERE: How to measure and interpret the conduction current in a.c. thin-film electroluminescent devices | 933 |
| G. Pitz, H. L. Hartnagel, K. Mause, F. Fiedler and D. Briggmann: Fully self-aligned N-p-n InGaAs/InP HBTs with evaluation of their microwave characteristics | 937 |
| R. Angelucci, S. Solmi, A. Armigliato, E. Gabilli, D. Govoni, M. Merli and A. Poggi: Arsenic ion implantation through Mo and Mo silicide layers for shallow junction formation | 941 |
| HUYNH VAN CONG and BUI DOAN-KHANH: Simple accurate general expression of the Fermi-Dirac integral F_j (a) for arbitrary a and $j > -1$ | 949 |
| D. B. M. KLAASSEN: A unified mobility model for device simulation—I. Model equations and concentration dependence | 953 |
| D. B. M. KLAASSEN: A unified mobility model for device simulation—II. Temperature dependence of carrier mobility and lifetime | 961 |
| M. H. JUANG and H. C. CHENG: Novel effects of heating rate on the activation/recrystallization of boron-implanted Si substrates | 969 |
| A. ČENYS, G. LASIENE and K. PYRAGAS: Spatiotemporal chaos in Gunn diodes in presence of impact ionization | 975 |
| P. VITANOV, T. DIMITROVA, R. KAMBUROVA and K. FILLJOV: Capacitance method for determination of LDD MOSFET geometrical parameters | 985 |
| S. S. KUCHERENKO and N. A. KUDRYASHOV: Photoelectric characteristics of a semiconductor diode with an abrupt junction at high photoexcitation levels | 993 |
| J. POPP and J. WENG: Measurement of transport parameters in heavily-doped emitters of bipolar transistors | 999 |
| Y. L. Le Coz and R. B. Iverson: A stochastic algorithm for high speed capacitance extraction in integrated circuits | 1005 |
| J. SZATKOWSKI and K. SIERAŃSKI: Simple interface-layer model for the nonideal characteristics of the Schottky-barrier diode | 1013 |

| Notes | |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|
| MINCHANG LIANG and MARK E. LAW: Influence of a selectively ion-implanted collector on bipolar transistor electrical characteristics | 101 |
| DAVID J. ROULSTON and JOEL M. McGregor: Effect of bandgap gradient in the base region of SiGe heterojunction bipolar transistors | 1019 |
| J. S. HAMEL, D. J. ROULSTON and C. R. SELVAKUMAR: Experimental method for extraction of emitter injection limited gain in bipolar transistors | 102 |
| P. CHATTOPADHYAY and B. RAYCHAUDHURI: New technique for the determination of series resistance of Schottky barrier diodes | 1023 |
| F. Fastow: Contact resistance and 1/f noise of Sn/In/HgCdTe contacts | 1025 |
| B. K. SINGH, T. ACHARJEE, A. N. DAW and R. N. MITTRA: Properties of amorphous Bi ₂ S ₃ -crystalline silicon heterojunctions | 1027 |
| SOFTWARE SURVEY SECTION | 1 |
| | |
| NUMBER 8 | |
| P. C. YANG, H. S. CHEN and SHENG S. LI: Measurements of interface state density in partially- and fully-depleted silicon-on-insulator MOSFETs by a high-low-frequency transconductance method | 1031 |
| J. CHEN, G. B. GAO and H. MORKOÇ: Comparative analysis of the high-frequency performance of $Si/Si_{1-x}Ge_x$ heterojunction bipolar and Si bipolar transistors | 1037 |
| Bruno Baccus: Impact of low-temperature transient-enhanced diffusion of dopants in silicon | 1045 |
| WILLIAM LIU and JAMES S. HARRIS: Current dependence of base-collector capacitance of bipolar transistors | 1051 |
| X. M. Li and M. J. Deen: Determination of interface state density in MOSFETs using the spatial profiling charge pumping technique | 1059 |
| A. CRUZ SERRA, H. ABREU SANTOS, A. MARTY, J. BAILBÉ and G. REY: Evidence of $\Gamma - \Gamma$ and $X - X$ coupling using a single abrupt isotype n -GaAs/Al _{0.5} Ga _{0.5} As heterojunction | 1065 |
| S. C. Jain, T. J. Gosling, J. R. Willis, R. Bullough and P. Balk: Theoretical comparison of the stability characteristics of capped and uncapped Ge_xSi_{1-x} strained epilayers | 1073 |
| L. P. CHEN, J. J. LOU, T. H. LIU, Y. M. PANG and S. J. YANG: Evaluation of low dark current InSb photovoltaic detectors | 1081 |
| D. Flandre and A. Terao: Extended theoretical analysis of the steady-state linear behaviour of accumulation-mode, long-channel p-MOSFETs on SOI substrates | 1085 |
| JEFFERY C. HUANG and IBRAHIM M. ABDEL-MOTALEB: Large-signal nonquasi-static model for single and double heterojunction bipolar transistors | 1093 |

| Contents | Xiii |
|----------|------|
| | |

| DOMINIQUE VUILLAUME and BRIAN S. DOYLE: Properties of hot carrier induced traps in MOSFETs characterized by the floating-gate technique | 1099 |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|
| ANTONIO G. M. STROLLO and GIANFRANCO VITALE: A closed-form two-dimensional model of a laser grooved solar cell | 1109 |
| NICCOLO' RINALDI, ANTONIO G. M. STROLLO and PAOLO SPIRITO: Two-dimensional modeling of current gain in downscaled bipolar transistors | 1119 |
| ROBERTO SUNG and MUKUNDA B. DAS: Photo-induced current measurement for the characterization of deep-level traps in lattice-matched MODFETs on InP substrate | 1129 |
| K. SADRA and B. G. STREETMAN: The coupled hole-phonon system and minority-electron transport in p-GaAs | 1139 |
| M. D. J. BOWYER, D. G. ASHWORTH and R. OVEN: Representation of ion implantation projected range profiles by Pearson distribution curves for silicon technology | 1151 |
| K. F. KNOTT: Study of sudden changes of large amplitude burst noise in bipolar transistors | 1167 |
| K. F. Knott: Statistical analysis of transients involved in moderate amplitude burst noise in bipolar junction transistors | 1173 |
| N. B. LUKYANCHIKOVA, N. P. GARBAR and M. V. PETRICHUK: Excess white noise in bipolar junction transistors | 1179 |
| D. TRIPATHI, P. C. SRIVASTAVA and S. CHANDRA: Studies on hydrogenated Pd/p-type Si diodes | 1185 |
| Notes | |
| C. Papadas, G. Ghibaudo, G. Pananakakis, C. Gounelle, P. Mortini and C. Riva: Influence of tunnel oxide thickness variation on the programmed window of FLOTOX EEPROM cells | 1195 |
| K. GMUCOVÁ: Investigation of the background in the spectrum of an MOS structure obtained by correlated DLTS | 1197 |
| Corrigenda | 1201 |
| SOFTWARE SURVEY SECTION: Sspice and TOPSIM | I |
| | |
| NUMBER 9 | |
| J. B. Kuang, S. Ratanaphanyarat, S. F. Chu and K. Seshan: Self-aligned vertical $p-n-p$ transistor: device characterization from room to cryogenic temperatures | 1203 |
| ZEYNEP ÇELIK-BUTLER and MIN YE: Prediction of electromigration failure in W/Al-Cu multilayered metallizations by $1/f$ noise measurements | 1209 |
| SZE-HIM NG and CHARLES SURYA: Studies of flicker noise in In _{0.53} Ga _{0.47} As/AlAs/InAs resonant tunneling diodes | 1213 |

xiv Contents

| BING-YUE TSUI and MAO-CHIEH CHEN: Contact resistivity of shallow junctions formed by implantation through Pt or PtSi | |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|
| MATS ROSLING, HENRY BLEICHNER, MANS LUNDQVIST and EDVARD NORDLANDER: A novel technique for the simultaneous measurement of ambipolar carrier lifetime and diffusion coefficient in silicon. | |
| J. Olsson, H. Norde and U. Magnusson: Investigation of the current-voltage behavior of a combined Schottky-p-n diode | |
| HUNG-SHENG CHEN and SHENG S. LI: Comparison of statistical variation of threshold voltage in bulk and SOI MOSFETs | |
| SHINICHI TAKIGAWA, KEN BACHER, LEWIS B. ARONSON and JAMES S. HARRIS JR: Design and performance of a low-threshold-current grating-coupled surface-emitting laser | |
| V. W. L. CHIN, T. OSOTCHAN and T. L. TANSLEY: On the calculation of electron mobility in In _{0.53} Ga _{0.47} As | 15 1 |
| Y. Pan: Electrical characterization of hole transport in heavily-doped shallow implanted emitters | 1 |
| M. B. ŽIVANOV and M. M. JEVTIĆ: Majority carrier mobility in highly-doped n-type Si | 1 |
| N. G. PATEL and P. G. PATEL: Thermoelectric cooling effect in a p-Sb ₂ Te ₃ -n-Bi ₂ Te ₃ thin film thermocouple | 1 |
| O. ROUX DIT BUISSON, G. GHIBAUDO and J. BRINI: Model for drain current RTS amplitude in small-area MOS transistors | 1 |
| HAE-SEOK CHO and JERRY G. FOSSUM: Polysilicon emitter design for scaled BiCMOS circuits | 1 |
| B. K. Jones and G. P. Taylor: Spectroscopy of surface states using the excess noise in a buried-channel MOS transistor | 1 |
| A. ORTIZ-CONDE, R. HERRERA, P. E. SCHMIDT, F. J. GARCÍA SÁNCHEZ and J. ANDRIAN: Long-channel silicon-on-insulator MOSFET theory | 1 |
| ANATOLY A. GRINBERG and SERGE LURYI: Diffusion in a short base | 1 |
| SHIH-CHIH CHEN, YAN-KUIN SU and CHUN-ZEN LEE: A study of current transport in $p-N$ heterojunctions | 1 |
| JICHENG ZHOU, QIANBAO ZHAN, ZHIPING FU, DONGLIANG LÜ, LIMIN GUAN and HUANGQI CHEN: Behavior of types A and B hole traps in n-type GaAs during long-period operation | 1 |
| S. J. Chua and S. H. Lee: Contact resistivity measurement using four circular contacts | 1 |
| F. COROMINA, A. PÉREZ-RODRÍGUEZ, J. R. MORANTE, J. MACÍA, M. A. LOURENÇO, K. P. HOMEWOOD and P. L. F. HEMMENT: Effects of electric field on photoconductive frequency resolved spectroscopy: analysis of silicon-on-insulator structures | 1 |
| HILMI ÜNLÜ: A thermodynamic model for determining pressure and temperature effects on the bandgap energies and other properties of some semiconductors | 1 |

| Contents | х |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|
| A. Ph. Akulov, V. V. Aphanasjev and V. A. Gurtov: Determination of the radiation-induced charge centroid in a MIS dielectric | 135 |
| A. V. GORBATYUK and P. B. RODIN: Effect of distributed-gate control on current filamentation in thyristors | 135 |
| X. B. CHEN, B. ZHANG and Z. J. LI: Theory of optimum design of reverse-biased $p-n$ junctions using resistive field plates and variation lateral doping | 136 |
| Notes T. C. Lu and J. B. Kuo: An analytical bandgap-narrowing-related current-gain model including concentration dependent diffusion coefficients for VLSI BJT devices | 137 |
| T. C. Lu and J. B. Kuo: A closed-form analytical BJT forward transit time model considering bandgap-narrowing effects and concentration-dependent diffusion coefficients | 137 |
| J. J. Liou: Effect of base grading on the Early voltage of HBTs | 137 |
| G. Sh. GILDENBLAT: Analytic d.c. characteristic of space-charge-limited currents with field-dependent mobility | 138 |
| Letter to the Editors J. M. McGregor, T. Manku and D. J. Roulston: Retraction: bipolar transistor base bandgap grading for minimum delay | 1383 |
| ANNOUNCEMENT | |
| SOFTWARE SURVEY SECTION | II |
| NUMBER 10 | |
| C. H. Su, Y. K. Su and F. S. Juang: GaSb/InGaSb strained-layer quantum wells by MOCVD | 1385 |
| S. Noor Mohammad: Unified model for drift velocities of electrons and holes in semiconductors as a function of temperature and electric field | 1391 |
| G. A. M. HURKX: An improved analytical description of the effect of velocity saturation on the collector current of a bipolar transistor | 1397 |
| H. THOMAS and J. K. Luo: Effect of plasma pre-treatment on Au/p-InP Schottky diodes | 1401 |
| KAI C. YUNG, KARNA J. WAHLSTRAND, JICK H. YEE and RAY P. MARIELLA JR: Theoretical investigation of the lasing characteristics of several GRIN-SCH quantum well lasers | 1409 |
| R. K. CHANANA, R. DWIVEDI and S. K. SRIVASTAVA: Silicon wafer cleaning with CF ₄ /H ₂ plasma and its effect on the properties of dry thermally grown oxide | 1417 |
| ABDÜLMECIT TÜRÜT, SEBAHATTIN TÜZEMEN, MUHAMMET YILDIRIM, BAHATTIN ABAY and MUSTAFA SAĞLAM: Barrier height enhancement by annealing Cr-Ni-Co alloy Schottky contacts on LEC GaAs | 1423 |
| | |

Z. Q. SHI and W. A. ANDERSON: Cryogenic processing of metal/GaAs Schottky diodes

1427

xvi Contents

| Z. J. Ma, P. T. Lai and Y. C. Cheng: Electrical characterization and simulation of substrate current in <i>n</i> -MOSFETs with nitrided/reoxidized-nitrided oxides as gate dielectrics. | 1433 |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|
| M. AHMAD and B. M. ARORA: Investigation of AuGeNi contacts using rectangular and circular transmission line model | 144 |
| G. SANCHEZ, J. GARRIDO, J. MARTINEZ, J. PIQUERAS, E. LORA and C. DOMINGUEZ: Electrical characteristics of aligned and transversally recrystallized SOI-MOS transistors | 1447 |
| E. PŁACZEK-POPKO and L. SZARO: Surface photovoltage in CdMnTe | 1451 |
| E. SIMOEN and B. DIERICKX: Kink-related low-frequency noise overshoot in Si NMOSTs at liquid helium temperatures | 1455 |
| S. LIANG, L. Z. HOU, T. Gu and C. A. T. SALAMA: Latch-up modeling of BiCMOS merged bipolar-MOS structures | 1461 |
| XIAOSONG LI and L. K. J. VANDAMME: 1/f Noise in series resistance of LDD MOSTs | 1471 |
| XIAOSONG LI and L. K. J. VANDAMME: 1/f Noise in MOSFET as a diagnostic tool | 1477 |
| ACHYUT KUMAR DUTTA, NARIHIRO MOROSAWA and YOSHINORI HATANAKA: Characteristics of a single a-SiC:H/a-Si:H heterostructure as a high-gain photodetector | 1483 |
| S. Lucherini: A high-threshold low-capacitance MOSFET | 1489 |
| Q. CHEN, M. WILLANDER, P. NAROZNY and H. DÄMBKES: Subthreshold current in submicron AlGaAs/GaAs MODFETs | 1493 |
| XIUMIAO ZHANG: Description of non-equilibrium phenomena in MIS device under linear voltage ramp bias | 1497 |
| H. BHIMNATHWALA and J. M. Borrego: Surface characterization of LEC SI-GaAs using photoreflectance with sub-bandgap excitation | 1503 |
| MING-BING CHANG, UMESH SHARMA and SHIH K. CHENG: An improved model for the erase operation of a FLOTOX EEPROM cell | 1513 |
| MING-BING CHANG, KO-MIN CHANG, CLINTON KUO and SHIH K. CHENG: A new scalable floating-gate EEPROM cell | 1521 |
| M. H. JUANG and H. C. CHENG: Formation of self-aligned $TiSi_2 p^+-n$ junctions by implanting BF_2^+ ions through thin Ti or SiO_2 film on Si substrate rapid thermal annealing | 1529 |
| M. H. Juang and H. C. Cheng: Characterization of silicided shallow n^+p junctions formed by P^+ implantation into thin Ti films on Si substrates | 1535 |
| T. ZIMMER, D. OURO BODI, J. M. DUMAS, N. LABAT, A. TOUBOUL and Y. DANTO: Kink effect in HEMT structures: a trap-related semi-quantitative model and an empirical approach for SPICE simulation | 1543 |
| A. L. ALEXANDROV, M. S. OBRECHT and G. V. GADIYAK: Efficient method for numerical modeling of thermal redistribution of interacting impurities under oxidizing ambient | 1549 |

| Notes J. B. Kuo, W. C. Lee and J. H. Sim: Back gate bias effects on the pull-down transient behavior in an ultra-thin SOI CMOS inverter operating at 300 and 77 K | 155 |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|
| C. C. Chang, T. C. Lu and J. B. Kuo: A closed-form analytical poly-emitter BJT forward transit time model considering bandgap-narrowing effects and concentration-dependent diffusion coefficients for poly-emitter BJT devices | 155 |
| YEN C. TZENG, PING C. YANG, CHING S. LEE and SHENG S. LI: Characterization of generation lifetime and deep-level defects in an $In_{0.4}Ga_{0.6}As\ p-i-n$ photodiode prepared by molecular beam epitaxy growth on GaAs | 156 |
| S. S. DE, A. K. GHOSH, T. K. PATTANAYAK, A. K. HAZRA and J. C. HALDAR: Studies on open-circuit photovoltage in heavily doped abrupt $P-N$ junction | 156 |
| Announcement | |
| SOFTWARE SURVEY SECTION | II |
| NUMBER 11 | |
| | |
| WILLIAM LIU: Effective lateral diffusion length in Npn AlGaAs/GaAs heterojunction bipolar transistors | 156 |
| WILLIAM LIU: Theoretical comparison of donor-density graded base and uniformly doped base in <i>Pnp</i> AlGaAs/GaAs heterojunction bipolar transistors | 1573 |
| TIEN SHENG CHAO, CHUNG LEN LEE and TAN FU LEI: A study of the interfacial layer of Al and Al(1% Si)—Si contacts using a zero-layer ellipsometry model | 1579 |
| A. SCHENK: A model for the field and temperature dependence of Shockley-Read-Hall lifetimes in silicon | 1585 |
| Tahui Wang, Ting-Hua Hsieh and Yi-Teh Chen: Quantum well geometrical effects on two-dimensional electron mobility | 1597 |
| C. BACKHOUSE and L. YOUNG: Deep level domain spectroscopy of low frequency oscillations in semi-insulating InP | 1601 |
| A. Solhi, M. Sahnoune, H. Lhermite and O. Bonnaud: Numerical simulation and experimental verification of the parameters determining the base current in an a-Si: H/c-Si emitter-base heterojunction bipolar transistor | 1609 |
| J. KASSABOV, E. ATANASSOVA, J. VASSILEVA and D. DIMITROV: Influence of u.v. radiation and source-to-bulk bias on the processes in the Si–SiO ₂ inversion channel | 1621 |
| J. Osvald: On barrier height inhomogeneities at polycrystalline metal-semiconductor contacts | 1629 |
| A. St. Denis, D. L. Pulfrey and A. Marty: Reciprocity in heterojunction bipolar transistors | 1633 |
| Ko-Ming Shih, D. P. Klemer and J. J. Liou: Current-voltage characteristics of | |
| submicrom GaAs MESFETs with nonuniform channel doping profiles | 1639 |

xviii Contents

| B. P. RAI, R. DWIVEDI and S. K. SRIVASTAVA: Negative bias instability in silicon dioxide films grown using oxidise-etch-oxidise process |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| T. SMEDES and J. A. VAN STEENWIJK: A new description of dual γ-factor threshold voltage with continuous second-order derivative |
| J. H. Sim and J. B. Kuo: A back-gate bias effect model considering the charge accumulation behavior above the field oxide for ultra-thin SOI NMOS devices |
| XIUMIAO ZHANG: Investigation of N^+-P diffused junction silicon solar cells |
| SWAPAN K. DATTA, K. MUKHOPADHYAY, S. BANDOPADHYAY and H. SAHA: An improved technique for the determination of solar cell parameters |
| S. R. Dhariwal and R. C. Sharma: Ramp recovery in $p-i-n$ diodes: general mathematical formulation and comparison with other methods of lifetime measurement |
| H. BLEICHNER, M. BAKOWSKI, M. ROSLING, E. NORDLANDER, J. VOBECKY, M. LUNDQVIST and S. Berg: A study of turn-off limitations and failure mechanisms of GTO thyristors by means of 2-D time-resolved optical measurements |
| JIANG ZHENG, JING WU and TONGLI WEI: Design and analysis of silicon bipolar transistors for low temperature operation |
| SOFTWARE SURVEY SECTION |
| NUMBER 12 |
| Purpose I McNusses The use of concreticed models to emploin the heliculeur of Ohmio |
| PATRICK J. McNally: The use of generalised models to explain the behaviour of Ohmic contacts to n-type GaAs |
| HENG-CHIH LIN, WEN-JYH SAH and SI-CHEN LEE: A common-gate CMOS inverter with <i>n</i> -channel amorphous silicon thin-film transistor formed on a crystalline PMOSFET |
| M. A. ABDALA and B. K. Jones: Correlation between trap characterisation by low frequency noise, mutual conductance dispersion, oscillations and DLTS in GaAs MESFETs |
| S. K. Lahiri, A. DasGupta, I. Manna and M. K. Das: A quasi-3D analytical threshold voltage model of small geometry MOSFETs |
| J. A. JIMENEZ-TEJADA, J. A. LOPEZ-VILLANUEVA, P. CARTUJO and J. E. CARCELLER: A non-destructive method to determine impurity-profiles in non-abrupt $p-n$ junctions with |
| deep levels |
| I. Thurzo, D. Pogány and K. Gmucová: A novel algorithm for higher order filtering in DLTS |
| I. Thurzo, D. Pogány and K. Gmucová: A novel algorithm for higher order filtering |
| I. THURZO, D. POGÁNY and K. GMUCOVÁ: A novel algorithm for higher order filtering in DLTS |

xix

| A. B. Joshi and D. L. Kwong: Comparison of <i>n</i> -MOSFET lifetime estimates based on GIDL enhancement and transconductance degradation as criteria | 175 |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|
| G. A. Armstrong and W. D. French: Simulation of ultra thin film SOI transistors using a non-local ballistic model for impact ionisation | 176 |
| C. W. Wang and C. H. Wu: A novel technique of analyzing multiexponential transients for DLTS spectra | 177 |
| HAOSHENG ZHOU and D. L. PULFREY: A new method for estimating the electron concentration in the 2-dimensional electron gas in MODFETs | 177 |
| F. BALESTRA: Analysis of the dependence of the subthreshold swing and the threshold voltage on the substrate voltage of thin-film SOI MOSFETs. Extraction of the interface state densities | 178 |
| SHENG-LYANG JANG, FONG-CHIN LIU and JIM-YAT WU: Current reversals in p-n-p transistors | 178 |
| M. SHUR, T. A. FJELDLY, T. YTTERDAL and K. LEE: Unified MOSFET model | 179 |
| SZE-HIM NG and CHARLES SURYA: A model for low frequency excess noise in Si-JFETs at low bias | 180 |
| CY. Su and HL. Hwang: Simulation and analysis of amorphous silicon image sensor having a $p-i-n$ structure | 181 |
| NARAIN D. ARORA, DAVID A. BELL and LARRY A. BAIR: An accurate method of determining MOSFET gate overlap capacitance | 181 |
| B. R. NAG, G. GHOSH and S. DHAR: A simple microwave method for monitoring the conductivity of semiconductor epitaxial layers | 182 |
| V. B. Orlov: Conductance fluctuations in solids caused by defect migration | 182 |
| Notes J. Grňo and R. Janota: Approximation of the Gaussian implanted profile by a rectangular profile | 183 |
| B. Paldus and D. J. Roulston: Optimum emitter parameters for maximum gain in uniformly doped NPN and PNP bipolar transistors | 183 |
| K. M. RAHMAN and M. R. KAHN: Interference type amplifier using intermodal interference in potential channel structures | 184 |
| REZA ROFAN, JACK CHURCHILL, CHENMING Hu and YUPIN FONG: Elimination of stress induced oxide leakage in textured tunneling oxide | 184 |
| SOFTWARE SURVEY SECTION | |

Reproduced with the permission of Pergamon Press Inc., by University Microfilms Inc. Duplication or resale without permission is prohibited.

